







Dimensions	215mm x 361mm x 3	15mm (h)	8.46in x 14.21in x 12.4in (h)		
Weight	12,2 kg		26,9 lb		
Voltage-Frequency	230V - 50Hz	- 50Hz 230V -		115V - 60Hz	
Current Consumption	1,7A	1,3A		1,9A	
Compressor Power	1/8 HP				
Power Consumption (Cooling)	150 W				
Power Consumption (Heating)	\		•		
Cooling Capacity *	220 W		750 Btu\h		
Min and Max Water Flow	300 l\h - 500 l/h		80 Usgal\h - 132 Usgal\h		
Air Flow	١				
Maximum Exchanger's Pressure	0,5 bar		7,25 psi		
Ambient Temperature Range	5°C - 38°C		41°F - 100°F		
Water Temperature Range	18°C - 22°C		64°F - 72°F		
Certification	CE		-		
Protection Grade	IPX4				
* the value reported refers to the following	condition: room temperature	30°C (86°F), v	water temperat	ture 20°C (68°F)	

Material:		Drawing:HY 150 — technical data				
Thickness:		File: HY_150_technical_drawing				
Finishing:		Your.code:		Code:		
Volume:		Tol.	<b>Scale:</b> 1:5	Date:	17/03/2017	
		Via A.Sansovino, 35			TCCO	
	Drawer:	48124 RAVENNA — ITALY Tel. +39 0544 408333 Fax 280084				
	Giulia	http://www.tecc				
AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ACHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES.WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.						

Drawer:

Modify: