

GroNode

	Interface communication	Ethernet
	Module Communications	Radio Frequency
	Firmware Updates	Ethernet
	Power outlet	5Vdc USB - 1000mA

Sensor

Temperature sensor range	-40°C ~ 80°C
Precision of the Readings (Temp)	± 0.5°C
Moisture range	0% ~ 100%
Moisture relative precision	± 2%

PowerBot

Module Communications	Radio Frequency	,
Firmware Updates	USB	
Universal outlets	х4	
Manual Switches	х4	
	Europe	USA
Input Voltage	230v AC	120v AC
Maximum power per outlet	2300W (10A)	1200W (10A)
Total maximum power	2300W (10A)	1200W (10A)

Connectors

Actuator outlets	X4
Maximum power actuators	5W (for DC output)
Sensor outlets	X4
Water measuring probe outlets	PH / EC / Temperature
Temperature range	0°C ~ 150°C
Temperature precision	± 0.5°C
PH range	0 ~ 14
PH precision	± 0.1

TankBot

Module Communications	Radio Frequency
Firmware Updates	USB
Compatibilidad de corriente	12Vdc ~ 24Vdc - min 500ma
Equipped with a transformer	12v DC 1000ma

SoilBot

Module Communications	Radio Frequency
Firmware Updates	USB
Compatibilidad de corriente	5Vdc USB - 500mA

Per informazioni più dettagliate contattaci su www.idroponica.it - info@idroponica.it - Tel. 06 92958411