

TLD-4

90 Watt ThinkGrow Model One LED Driver with Four Spectrum Control Channels

The TLD-4, is a modular plug-and-play LED driver that is designed to operate a single 90-watt LED bar. Since the TLD-4 is a modular driver, it can be combined with additional TLD-4 drivers to create a complete lighting system that can fit into any size space, and provide up to 1400 umol of light. It features four spectrum control channels and can be connected to a TrolMaster HCS or TCS controller to allow for remote control and independent settings for each of the four channels. That provides the ability to have customized lighting spectrum and timing control. The TLD-4 works with the 4ft long TLB-1 or 5ft long TLB-2 LED light bars from ThinkGrow.



Specifications

TLD-4

Input Power

Input Power 90W

Input Voltage

Voltage Autosensing 100-277V~,50/60Hz

IP Water Resistance

IP IP56

Amperage Draw

Amperage Draw 0.77A@120V /
0.43A@208V /
0.39A@230V /
0.39A@240V /
0.35A@277V

No. of LEDs in a Configuration

Maximum Connection 120V : Max. 11pcs
208V : Max. 19pcs
230V : Max. 21pcs
240V : Max. 22pcs
277V : Max. 25pcs

Working Environments

Temperature 32-104°F (0-40°C)

Humidity 5~95%RH

Dimensions

Size 15.15"(L) x 4.07"(W) x 3.58"(H)

Weight

Gross Weight 2.03lbs /0.92kg

Installation

TLD-4

